

# Material Safety Data Sheet

## Freeman 1080Part A

Date of Preparation: June 18, 2009

### Section 1 Chemical Product and Company Identification

**Product/Chemical Name:** Freeman 1080 Part A  
**Chemical Family:** Isocyanate  
**CAS Number:** N/A  
**Other Designations:** N/A  
**General Use:** N/A  
**Manufacturer:** Freeman Manufacturing and Supply Company, 1101 Moore Road, Avon, OH 44011  
Phone (440) 934-1902, FAX (440) 934-7200, Hours of Operation 8-5,  
Emergency phone number 1-800-424-9300

HMIS	
<b>H</b>	2
<b>F</b>	1
<b>R</b>	1
<b>PPE</b> Sec.8.	

### Section 2 Composition/Information on Ingredients

Ingredient Name	CAS Number
4,4' Methylene bis(phenylisocyanate)	101-68-8

Ingredient	OSHA		ACGIH	
	PEL	STEL	TLV	STEL
4,4' Methylene bis(phenylisocyanate)	0.005 ppm	0.02 ppm	0.005 ppm	none estab

### Section 3 Hazards Identification

#### ☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Irritant, Sensitizer

#### Potential Health Effects

**Primary Entry Routes:** Skin; Inhalation from heated vapors.

**Acute Effects:**

**Inhalation:** Irritates the respiratory tract

**Eye:** Causes irritation

**Skin:** Causes irritation

**Ingestion:** Swallowing can cause abdominal irritation, nausea, vomiting, and diarrhea.

**Medical Conditions Aggravated by Long-Term Exposure:** Persons with severe skin problems should avoid use.

**Chronic Effects:** No known chronic effects associated with this material.

**Carcinogenicity:** IARC, NTP, and OSHA do not list any component as carcinogenic.

### Section 4 First Aid Measures

**Inhalation:** Remove to fresh air. If breathing is difficult, give oxygen and/or artificial respiration.

**Eye Contact:** Flush with plenty of water for 15 minutes and get medical attention.

**Skin Contact:** Wash thoroughly with soap and water. Remove contaminated clothing and launder before reuse.  
Destroy contaminated shoes.

**Ingestion:** If conscious, give 2-4 glasses of water to drink. Do not induce vomiting. Get medical attention.

## Freeman 1080Part A Side

### Section 5 Fire Fighting Measures

**Flash Point:** 390 °F (199 °C)

**Flash Point Method:** COC


**LEL:** Not established

**UEL:** Not established

**Extinguishing Media:** Foam, water, CO<sub>2</sub>, or dry chemical

**Fire-Fighting Equipment:** Use self-contained breathing apparatus.

**Fire and Explosion Hazards:** Decomposition and combustion products may be toxic.



### Section 6 Accidental Release Measures

**Spill /Leak Procedures:** Stop spill at source. Dike area and contain. Clean up remainder with absorbent materials such as sand or vermiculite. Mop up and dispose of.

### Section 7 Handling and Storage

**Handling & Storage:** Use with adequate ventilation. Avoid prolonged breathing of vapor. Avoid prolonged or repeated contact with skin. Wear safety goggles or face shield. Wear gloves, apron and footwear impervious to this material. Wash clothing before reuse. Store at ambient temperatures.. When resealing cans, use a nitrogen purge (Polyurethane Protectant). Keep container tightly closed and upright when not in use to prevent leakage.

### Section 8 Exposure Controls/Personal Protection

**Ventilation:** Local exhaust recommended. General mechanical is acceptable. Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2).

**Respiratory Protection:** Use a NIOSH approved respirator when vapor/mist exposure is likely.

**Eye Protection:** Wear splash-proof chemical goggles.

**Skin Protection:** Wear impermeable gloves.

**Safety Stations:** Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

**Comments:** Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

### Section 9 Physical and Chemical Properties

**Appearance and Odor:** Liquid, Clear yellow to slightly turbid, musty odor

**Vapor Pressure:** <0.00001 @ 25°C

**Vapor Density (Air=1):** 8.6

**Specific Gravity (H<sub>2</sub>O=1, at 4 °C):** 1.18

**Water Solubility:** Reacts with water

**Boiling Point:** 392°F (200°C)

**% Volatile:** Nil

**Evaporation Rate:** Not Applicable

**pH:** Not Applicable

### Section 10 Stability and Reactivity

**Stability:** This product is stable at room temperature in closed containers under normal storage and handling conditions.

**Polymerization:** Hazardous polymerization can occur.

**Chemical Incompatibilities:** Strong bases, water, amines, alcohols

**Conditions to Avoid:** Avoid contamination with water and other materials that react with Isocyanates. Avoid accidental mixing with polyols.

**Hazardous Decomposition Products:** Carbon dioxide, carbon monoxide, oxides of nitrogen, traces of HCN, MDI vapors.

**Section 11 Toxicological Information**

**Acute Inhalation Exposure Effects:** Respiratory irritant.  
**Skin :** Irritant.  
**Eye:** Irritant.  
**Carcinogenicity:** IARC, NTP, and OSHA do not list any components as carcinogens.

**Section 12 Ecological Information**

No Known evidence of adverse effects from available information

**Section 13 Disposal Considerations**

**Disposal:** Use safety containers for disposal. Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations

**Section 14 Transport Information**

**DOT Transportation Data (49 CFR 172.101):**

**Shipping Name:** Liquid Plastic    N.O.I., Non-Regulated

**Section 15 Regulatory Information**

**US Federal Regulations:**

OSHA (Occupational Safety and Health Act): This Material Safety Data Sheet has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. This product is considered to be a hazardous chemical under that standard.

RCRA (Resource Conservation and Recovery Act): Not a hazardous waste under RCRA (40 CFR 261).

SARA 311/312 Codes: Acute Health, Fire.

SARA Toxic Chemical (40 CFR 372.65): This product contains the following toxic chemical subject to the reporting requirements of Section 313 of SARA Title III of 1986 and of 40 CFR 372.

4,4' Methylene bis(phenylisocyanate) CAS # 101-68-8, 70% by wt. Max

TSCA Inventory Status: All ingredients listed on TSCA inventory requirements.

**State Regulations:**

4,4' Methylene bis(phenylisocyanate) CAS # 101-68-8 may be found on both the New Jersey and the Pennsylvania Right to Know lists.

**Section 16 Other Information**

**Disclaimer:** The following supersedes Buyer's documents. SELLER MAKES NO REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No statements herein are to be construed as inducements to infringe any relevant patent. Under no circumstances shall Seller be liable for incidental, consequential or indirect damages for alleged negligence, breach of warranty, strict of liability arising in connection with the product(s). Buyer's sole remedy and Seller's sole liability for any claims shall be Buyer's purchase price. Data and results are based on controlled lab work and must be confirmed by Buyer by testing for its intended conditions of use. The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implantation within the human body is intended.

# Material Safety Data Sheet

## Freeman 1080 Part B

Date of Preparation: June 18, 2009

### Section 1 Chemical Product and Company Identification

**Product/Chemical Name:** Freeman 1080 Part B  
**Chemical Family:** Polyol  
**CAS Number:** N/A  
**Other Designations:** N/A  
**General Use:** N/A  
**Manufacturer:** Freeman Manufacturing and Supply Company, 1101 Moore Road, Avon, OH 44011  
Phone (440) 934-1902, FAX (440) 934-7200, Hours of Operation 8-5,  
Emergency phone number 1-800-424-9300

HMIS	
<b>H</b>	1
<b>F</b>	1
<b>R</b>	1
<b>PPE</b> Sec.8.	

### Section 2 Composition/Information on Ingredients

Ingredient Name	CAS Number
Urethane Polyol	Proprietary

Ingredient	OSHA		ACGIH		Vapor
	PEL	STEL	TLV	STEL	Pressure
Urethane Polyol	none estab.	none estab.	none estab.	none estab.	N/A

### Section 3 Hazards Identification

#### ☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Causes eye, skin, and respiratory irritations.

#### Potential Health Effects

**Primary Entry Routes:** Skin; Inhalation from heated vapors.

**Acute Effects:**

**Inhalation:** Irritates the respiratory tract

**Eye:** Causes irritation

**Skin:** Causes irritation

**Ingestion:** Swallowing can cause abdominal irritation, nausea, vomiting, and diarrhea.

**Medical Conditions Aggravated by Long-Term Exposure:** Persons with severe skin problems should avoid use.

**Chronic Effects:** No known chronic effects associated with this material.

**Carcinogenicity:** IARC, NTP, and OSHA do not list any components of this product as a carcinogen.

### Section 4 First Aid Measures

**Inhalation:** Remove to fresh air. If breathing is difficult, give oxygen and/or artificial respiration.

**Eye Contact:** Flush with plenty of water for 15 minutes and get medical attention.

**Skin Contact:** Wash thoroughly with soap and water. Remove contaminated clothing and launder before reuse.  
Destroy contaminated shoes.

**Ingestion:** If conscious, give 2-4 glasses of water to drink. Do not induce vomiting. Get medical attention.

## Freeman 1080 Part B Side

### Section 5 Fire Fighting Measures

**Flash Point:** >365°F (>185 °C)

**Flash Point Method:** PMCC


**LEL:** Not established

**UEL:** Not established

**Extinguishing Media:** Foam, water fog, CO<sub>2</sub>, or dry chemical

**Fire-Fighting Equipment:** Use self-contained breathing apparatus.

**Fire and Explosion Hazards:** Decomposition and combustion products may be toxic.



### Section 6 Accidental Release Measures

**Spill /Leak Procedures:** Stop spill at source. Dike area and contain. Clean up remainder with absorbent materials such as sand or vermiculite. Mop up and dispose of.

### Section 7 Handling and Storage

**Handling & Storage:** Use with adequate ventilation. Avoid prolonged breathing of vapor. Avoid prolonged or repeated contact with skin. Wear safety goggles or face shield. Wear gloves, apron and footwear impervious to this material. Wash clothing before reuse. Store at ambient temperatures.. When resealing cans, use a nitrogen purge (Polyurethane Protectant). Keep container tightly closed and upright when not in use to prevent leakage.

### Section 8 Exposure Controls/Personal Protection

**Ventilation:** Local exhaust recommended. General mechanical is acceptable. Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2).

**Respiratory Protection:** Use a NIOSH approved respirator when vapor/mist exposure is likely.

**Eye Protection:** Wear splash-proof chemical goggles.

**Skin Protection:** Wear impermeable gloves.

**Safety Stations:** Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

**Comments:** Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

### Section 9 Physical and Chemical Properties

**Appearance and Odor:** Liquid, white, mild odor

**Vapor Pressure:** Not determined

**Vapor Density (Air=1):** Not determined

**Specific Gravity (H<sub>2</sub>O=1, at 4 °C):** 1.04

**Water Solubility:** Slight

**Boiling Point:** Not determined

**% Volatile:** Nil

**Evaporation Rate:** Not determined

### Section 10 Stability and Reactivity

**Stability:** Stable.

**Conditions to Avoid:** Contamination with materials containing active NCO compounds, excessive heat for prolonged period.

**Chemical Incompatibilities:** Strong oxidizing agents, acids, metal-organic compounds.

**Hazardous Decomposition Products:** Combustion may form toxic materials, such as carbon dioxide, carbon monoxide.

**Hazardous Polymerization:** Will not occur. Avoid inadvertent mixture of A and B parts.

## Freeman 1080 Part B Side

### Section 11 Toxicological Information

**Acute Inhalation Exposure Effects:** Respiratory irritant.

**Skin Irritation:** Irritant.

**Eye Irritation:** Irritant.

**Carcinogenicity:** IARC, NTP, and OSHA do not list any components of this product as a carcinogen.

### Section 12 Ecological Information

No Known evidence of adverse effects from available information

### Section 13 Disposal Considerations

**Disposal:** Use safety containers for disposal. Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations

### Section 14 Transport Information

#### DOT Transportation Data (49 CFR 172.101):

**Shipping Name:** Liquid Plastic, N.O.I., Non-Regulated

### Section 15 Regulatory Information

#### US Federal Regulations:

OSHA (Occupational Safety and Health Act): This Material Safety Data Sheet has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. This product is considered to be a hazardous chemical under that standard.

RCRA (Resource Conservation and Recovery Act): Not a hazardous waste under RCRA (40 CFR 261).

SARA 311/312 Codes:

SARA Toxic Chemical (40 CFR 372.65): This product contains the following toxic chemical subject to the reporting requirements of Section 313 of SARA Title III of 1986 and of 40 CFR 372. None

TSCA Inventory Status: All ingredients listed on TSCA inventory requirements.

#### State Regulations:

CA Proposition 65 No component listed

### Section 16 Other Information

**Disclaimer:** The following supersedes Buyer's documents. SELLER MAKES NO REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No statements herein are to be construed as inducements to infringe any relevant patent. Under no circumstances shall Seller be liable for incidental, consequential or indirect damages for alleged negligence, breach of warranty, strict of liability arising in connection with the product(s). Buyer's sole remedy and Seller's sole liability for any claims shall be Buyer's purchase price. Data and results are based on controlled lab work and must be confirmed by Buyer by testing for its intended conditions of use. The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implantation within the human body is intended.